

## Specification Data Sheet

### Iconic WPC Hybrid Flooring Click Profile for Floating Install, 1520 x 228 x 7.5mm & 1520 x 180 x 7.5mm

ICONIC WPC Hybrid flooring represents next generation manufacturing techniques utilising sustainable Wood Plastic Composites (WPC) to form a robust, interior waterproof flooring. The visual décors provide realistic embossed timber textures and colours in both Australian timber species and a classic Oak palette. ICONIC is coated with a matte finish, scratch resistant water-based PU lacquer for everyday scuff resistance.

The planks include a stabilising balance layer with an attached **1.5mm** cross-linked IXPE acoustic foam layer that delivers excellent noise reduction capabilities to enhance walking comfort and minimise sound transmission. **Interior use only.**

**Key Features;** Interior waterproof, can be installed in wet areas including bathrooms and laundry. Delivers superior dimensional stability. Excellent for renovations over existing ceramic tiles, minimal telegraphing. High impact **0.5mm** resistance wear layer. Two available plank widths, **Super Width 228mm** and **Classic Width 180mm**. Click for easy floating install.

**Colour Range;** Classic Australian Timber species, **180mm** & a contemporary colour Oak palette, **228mm**.

**Description;** Hybrid construction, WPC core, **0.5mm** Vinyl décor layer, with an attached **1.5mm** acoustic sound pad.

**Grade & Surface;** Slight embossed surface texture, matte sheen coating, non-toxic PU lacquer for everyday wear & tear.

**Size & Length;** **228mm** width, **7.5mm** thickness, **1520mm** length & **180mm** width, **7.5mm** thickness, **1520mm** length.

**Quantity;** **228mm** width, **2.080m<sup>2</sup>** / carton, approx. 76 cartons / pallet. **180mm** width, **2.189m<sup>2</sup>** / carton, approx. 70 cartons / pallet.

**Profile;** Angle / Angle Unilin Click for floating install. **Micro Bevelled Edges.**

**Acoustic outcome;** Test Result including attached underlay, **L<sup>n</sup>T<sub>w</sub> 39**.

**Fire Test Data;** AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **9.6kW/m<sup>2</sup>**. Mean Smoke Development, **304 percent minutes**.

**Slip Resistance;** In accordance with AS/NZS 4586; 2013 **P3** for Wet Pendulum test & **R10** for the Oil-Wet Inclining test.

**VOC Emissions;** **E1**, (Below World Health Organisation Levels). ICONIC is Respirable Silica Dust & Phthalate free.

**Accessories;** Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, [info@preferencefloors.com.au](mailto:info@preferencefloors.com.au) or a local sales office.

[www.preferencefloors.com.au](http://www.preferencefloors.com.au)

#### Adelaide (SA)

t +61 8 8262 2774  
sa@preferencefloors.com.au

#### Brisbane (QLD)

t +61 7 3875 1688  
qld@preferencefloors.com.au

#### Melbourne (VIC)

t +61 3 9794 5111  
vic@preferencefloors.com.au

#### Perth (WA)

t +61 8 9471 7785  
wa@preferencefloors.com.au

#### Sydney (NSW)

t +61 2 9738 1188  
sales@preferencefloors.com.au